

List of Figures

Figure C2-1	Rehabilitation Objectives	2-4
Figure C2-2	Surface Showing Relative Costs of Various Rehabilitation Objectives	2-4
Figure C2-3	Performance and Structural Deformation Demand for Ductile Structures	2-8
Figure C2-4	Performance and Structural Deformation Demand for Nonductile Structures	2-8
Figure C2-5	Idealized Force versus Displacement Backbone Curve	2-34
Figure C3-1	Examples of Torsional Redundancy and Torsional Stiffness	3-3
Figure C3-2	Diaphragm and Wall Displacement Terminology	3-6
Figure C3-3	Plausible Force Distribution in a Flexible Diaphragm	3-6
Figure C3-4	Influence of Spectral Shape on SSI Effects	3-7
Figure C3-5	Multidirectional Effects on Calculation of Design Actions	3-8
Figure C3-6	Hinge Formation Along Beam Span	3-11
Figure C3-7	Post-Earthquake Residual Gravity Load Capacity	3-11
Figure C3-8	Basis for the Linear Static Procedure	3-13
Figure C3-9	Relation between R and C_I	3-14
Figure C3-10	Increased Displacements Due to Pinched Hysteresis	3-15
Figure C3-11	Sample Inertia Force Distributions	3-16
Figure C3-12	Limitations of the NSP Illustrated with Story Ductility Demand, Amplification of Base Shear, and Moment Envelopes	3-19
Figure C3-13	Identification of Potential Plastic Hinge Locations	3-22
Figure C3-14	Base Shear Versus Displacement Relations	3-24
Figure C3-15	Effects of Negative Stiffness on Displacement Amplification	3-25
Figure C3-16	Stiffness Calculations for Estimating Building Response	3-26
Figure C3-17	Spectral Acceleration and Displacement Curves	3-27
Figure C3-18	Spectral Demand Curves	3-28
Figure C3-19	Force-Displacement Relations of MDOF Building and Equivalent SDOF System	3-29
Figure C3-20	Shape Vectors used in Sensitivity Study	3-31
Figure C3-21	Sensitivity to the Choice of Shape Vector	3-31
Figure C3-22	Checking for Force-Controlled Actions	3-33
Figure C3-23	Basis for m Factor (using M as Representative of a Deformation-Controlled Action)	3-35
Figure C3-24	Frame Evaluation - Beam Information	3-36
Figure C3-25	Frame Evaluation - Column Information	3-38
Figure C3-26	Evaluation of a Multibay Frame	3-39
Figure C4-1	General Procedure: Evaluating Foundations and Geotechnical Information	4-2
Figure C4-2	Schematic Diagrams of Surface Fault Displacement (modified from Slemmons, 1977)	4-6
Figure C4-3	Features Commonly Found along Active Strike-Slip Faults (modified from Slemmons, 1977)	4-7
Figure C4-4	Relationship Between Cyclic Stress Ratio Causing Liquefaction and $(N_I)_{60}$ values for $M = 7.5$ Earthquakes (from Seed et al., 1985)	4-8
Figure C4-5	Comparing Site $(N_I)_{60}$ Data from Standard Penetration Tests with Critical $(N_I)_{60}$ Values Calculated using the Seed-Idriss Procedure	4-9

Figure C4-6	Lateral Spread Before and After Failure (from Youd, 1984)	4-9
Figure C4-7	Typical Relationships for Sand and Gravel (from Marcuson and Hynes, 1990)	4-10
Figure C4-8	Relationship among Cyclic Stress Ratio, $(N_I)_{60}$, and Volumetric Strain for Saturated Clean Sands (from Tokimatsu and Seed, 1987)	4-11
Figure C4-9	Correlation for Volumetric Strain, Shear Strains, and $(N_I)_{60}$ (from Tokimatsu and Seed, 1987).	4-12
Figure C4-10	Conceptual Schemes to Resist Liquefaction-Induced Settlement or Bearing Capacity Reductions	4-14
Figure C4-11	Conceptual Schemes to Resist Liquefaction-Induced Lateral Spreading	4-14
Figure C4-12	Schematic Diagram of Types of Grouting (from notes taken during a 1989 GKN Hayward Baker, Inc., Ground Modification Seminar)	4-15
Figure C4-13	Bearing Capacity Factors (calculated from Vesic, 1975)	4-17
Figure C4-14	Footing Lateral Stiffness and Capacity Components	4-18
Figure C4-15	Load-Displacement Relationship for Spread Footing	4-19
Figure C4-16	Analytical Models for Spread Footing	4-19
Figure C4-17	Rocking of Shear Wall on Strip Footing	4-20
Figure C4-18	Shear Wall and Frame Example	4-21
Figure C4-19	Foundation Stiffness and Strength Properties	4-23
Figure C4-20	Structural Model, One Exterior Wall of Two-Story Masonry Building	4-24
Figure C4-21	Schematic Representation of Axial Pile Loading (Matlock and Lam, 1980)	4-25
Figure C4-22	Graphical Solution for Axial Pile Stiffness (Lam et al., 1991)	4-26
Figure C4-23	Load-Displacement Characteristics under Axial Loading (Lam and Martin, 1986)	4-27
Figure C4-24	Pile Footing Configuration for Moment-Rotation Study (Lam, 1994)	4-28
Figure C4-25	Axial Load-Displacement Curve for Single Pile (Lam, 1994)	4-29
Figure C4-26	Cyclic Moment-Rotation and Settlement-Rotation Solutions (Lam, 1994)	4-29
Figure C5-1	Cast and Wrought Iron Column Sections	5-2
Figure C5-2	Riveted T-Stub Connection	5-4
Figure C5-3	M - θ Relationships for FR and PR Connections	5-9
Figure C5-4	Model of PR Frame	5-13
Figure C5-5	Hysteresis of PR Connection	5-13
Figure C5-6	Frame Subassemblage	5-14
Figure C5-7	Bolted Flange Plate Connection	5-16
Figure C5-8	Welded Flange Plate Connection	5-16
Figure C5-9	End Plate Connection	5-17
Figure C5-10	T-Stub Connection	5-18
Figure C5-11	Prying Action in T-Stub Connection	5-19
Figure C5-12	Clip Angle Connection	5-21
Figure C5-13	Forces in Clip Angle	5-23
Figure C5-14	Moment Resistance by Clip Angle Connection	5-23
Figure C5-15	Effects of Web Rivets and Slab	5-24
Figure C5-16	Response of Braced Story with Moment Frame Backup	5-26
Figure C5-17	Typical Load versus Axial Deformation Behavior for a Brace	5-27
Figure C5-18	Axial Hysteresis Model—Load Starting in Tension	5-27
Figure C5-19	Stiffness Coefficients for a Link of Length e	5-29

Figure C5-20	Shear-Moment Interaction	5-30
Figure C5-21	Link Rotation Angle	5-30
Figure C5-22	Deformation Capacity Definitions for a Link	5-31
Figure C5-23	Models for Pile Analysis	5-36
Figure C5-24	Equivalent Cantilever Model for Piles	5-37
Figure C6-1	Evaluation of Beam Moment Demands of All Sections Along Span	6-18
Figure C6-2	Determination of Correct Locations of Beam Flexural Plastic Hinges	6-19
Figure C6-3	Sources of Flexibility in a Wall	6-19
Figure C6-4	Typical Load-Deformation Relations Suitable for Nonlinear Static Procedure	6-21
Figure C6-5	Relation Between Beam Embedded Bar Stress Capacity and Coexisting Tensile Stress in Adjacent Column Longitudinal Reinforcement	6-24
Figure C6-6	Flexural Failure Mechanisms of Reinforced Concrete Frames	6-26
Figure C6-7	Takeda Hysteresis Model	6-28
Figure C6-8	Sample Load-Deformation Relations for Reinforced Concrete Beams, Columns, and Beam-Column Connections	6-29
Figure C6-9	Sample Load-Deformation Relations for Prestressed, Partially-Prestressed, and Reinforced Beams	6-35
Figure C6-10	Models for Slab-Column Framing	6-36
Figure C6-11	Sample Load-Deformation Relations for Reinforced Concrete Slab-Column Connections	6-37
Figure C6-12	Slab Distortion in Flat-Plate Connection under Lateral Load	6-38
Figure C6-13	Eccentric Shear Stress Model	6-38
Figure C6-14	Load-Deformation Relation for Masonry-Infilled Reinforced Concrete Frame	6-41
Figure C6-15	Shear Wall Base Moment versus First-Story Rotation Relationship (Specimen W-1, Ali and Wight, 1991)	6-46
Figure C6-16	Shear Wall Base Moment versus Base Rotation Relationship (Specimen RW1, Thomsen and Wallace, 1995)	6-46
Figure C6-17	Lateral Load versus Top Displacement Relationship (Paulay, 1986)	6-48
Figure C6-18	Shear Wall Base Moment versus Base Rotation Relationship (Specimen TW2, Thomsen and Wallace, 1995)	6-48
Figure C6-19	Shear Wall Base Moment versus Base Rotation Relationship (Specimen TW1, Thomsen and Wallace, 1995)	6-49
Figure C6-20	Analytical Moment-Curvature Relationship for Rectangular and T-Shaped Wall Sections (Thomsen and Wallace, 1995)	6-49
Figure C6-21	Lateral Shear Force versus Top Displacement of Shear Wall Specimen 1 (Saatcioglu, 1995)	6-50
Figure C6-22	Lateral Shear Force versus Top Displacement of Shear Wall Specimen 4 (Saatcioglu, 1995)	6-50
Figure C6-23	Lateral Load versus Chord Rotation Relationship Beam 315 (Paulay, 1971b)	6-51
Figure C6-24	Lateral Load versus Chord Rotation Relationship Beam 312 (Paulay, 1971b)	6-51
Figure C6-25	Lateral Load versus Chord Rotation Relationship Beam 316 (Paulay, 1971b)	6-52
Figure C7-1	Compression Strut Analogy–Concentric Struts	7-28
Figure C7-2	Compression Strut Analogy–Eccentric Struts	7-29
Figure C7-3	Compression Strut Analogy–Perforated Infills	7-29
Figure C7-4	Estimating Forces Applied to Columns	7-31
Figure C7-5	Estimating Forces Applied to Beams	7-32

Figure C9-1	Center Bearing Displacement (Mean of Nine Analyses) in Eight-Story Building with Hysteretic Isolation System	9-7
Figure C9-2	Distribution of Shear Force (Mean of Nine Analyses) with Height in Eight-Story Building with Hysteretic Isolation System	9-7
Figure C9-3	Comparison of Distribution of Shear Force with Height in Eight-Story Building with Hysteretic and Linear Viscous Isolation System	9-8
Figure C9-4	Idealized Hysteretic Force-Displacement Relation of Elastomeric Bearing	9-9
Figure C9-5	Force-Displacement Loops of a High-Damping Rubber Bearing	9-9
Figure C9-6	Tangent Shear Modulus and Effective Damping Ratio of High-Damping Rubber Bearing	9-10
Figure C9-7	Analytical Force-Displacement Loops of High-Damping Rubber Bearing	9-11
Figure C9-8	Idealized Force-Displacement Loops of Sliding Bearings	9-12
Figure C9-9	Parameters in Model of Friction of Sliding Bearings	9-13
Figure C9-10	Coefficient of Friction of PTFE-based Composite in Contact with Polished Stainless Steel at Normal Temperature	9-14
Figure C9-11	Definition of Effective Stiffness of Seismic Isolation Devices	9-15
Figure C9-12	Energy Dissipation Nomenclature	9-23
Figure C9-13	Effect of Energy Dissipation on the Force-Displacement Response of a Building	9-23
Figure C9-14	Idealized Force-Displacement Loops of Displacement-Dependent Energy Dissipation Devices	9-25
Figure C9-15	Idealized Force-Displacement Loops of Velocity-Dependent Energy Dissipation Devices	9-25
Figure C9-16	Idealized Force-Displacement Loops of Energy Dissipation Devices with Recentering Capability	9-25
Figure C9-17	Idealized Force-Displacement Relation for a Viscoelastic Solid Device	9-26
Figure C9-18	Normalized Effective Stiffness (G') and Damping Coefficient (G''/ω) of Viscoelastic Solid Device	9-26
Figure C9-19	Model for Viscoelastic Energy Dissipation Device Behavior	9-26
Figure C9-20	Properties of Viscoelastic Solid Device Predicted by Standard Linear Solid Model	9-27
Figure C9-21	Maxwell Model for Fluid Viscoelastic Energy Dissipation Devices	9-27
Figure C9-22	Construction of Response Spectrum for Damping Higher than 5%	9-33
Figure C9-23	Spectral Capacity and Demand Curves for Rehabilitated One-Story Building	9-36
Figure C9-24	Representation of the Push-over Curve and Hysteresis Loops	9-36
Figure C9-25	Definition of Parameters for Simplified Nonlinear Analysis of One-Story Building with Viscoelastic Energy Dissipation System (EDS)	9-38
Figure C9-26	Definition of Angle and Relative Displacement of Energy Dissipation Device	9-38
Figure C9-27	Definition of Parameters for Simplified Nonlinear Analysis of One-Story Building with Viscous Energy Dissipation System (EDS)	9-39
Figure C9-28	Sample Building Information	9-42
Figure C9-29	Loads on Building and LSP Actions in a Selected Component	9-45
Figure C9-30	Loads on Building and LDP Actions in a Selected Component	9-47
Figure C9-31	NSP Method 2 Schematic	9-48
Figure C9-32	Force-Displacement Relations for Sample Building	9-48
Figure C9-33	NSP Response Estimates, Method 2, Modal Pattern (a) Target Roof Displacement of 4.2 inches (b) Target Roof Displacement of 5.1 inches	9-50
Figure C9-34	Elements of Passive Control System	9-53

Figure C9-35	Elements of Active Control System	9-54
Figure C9-36	Details of Control System of Active Bracing System	9-54
Figure C9-37	Details of Control System of Semi-Active Energy Dissipation Bracing System	9-55
Figure C11-1	Nonstructural Evaluation Procedure	11-8

